



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 1 / 10

### Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name **THERMOFLEX ONE**

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Membrana impermeabilizzante termo-riflettente**

##### 1.3. Details of the supplier of the safety data sheet

Name **SPIVER S.r.l.**  
Full address **Contrada Babbaurra SS 122**  
District and Country **93100 CALTANISSETTA (CL)**  
**ITALY**  
Tel. **+39 0934 577791**  
Fax **+39 0934 588795**

e-mail address of the competent person responsible for the Safety Data Sheet **info@spiver.it**

##### 1.4. Emergency telephone number

For urgent inquiries refer to **+39 0934 577791**

#### SECTION 2. Hazards identification

##### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1A

H317

May cause an allergic skin reaction.

##### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:

**H317**

May cause an allergic skin reaction.

**EUH208**

Contains: **2-metil-4-isotiazolin-3-one**  
**1,2-benzisothiazol-3(2H)-one**

May produce an allergic reaction.

Precautionary statements:

**P280**

Wear protective gloves.

**P261**

Avoid breathing dust / fume / gas / mist / vapours / spray.

**P333+P313**

If skin irritation or rash occurs: Get medical advice / attention.

**P362+P364**

Take off contaminated clothing and wash it before reuse.



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 2 / 10

### SECTION 2. Hazards identification ... / >>

**Contains:** 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

| Identification  | x = Conc. %  | Classification 1272/2008 (CLP)  |
|---|--------------|---|
| <b>QUARTZ</b>   |              |   |
| CAS   | 14808-60-7   | $1,5 \leq x < 2$ STOT RE 2 H373   |
| EC  | 238-878-4    |   |
| INDEX   |              |   |
| <b>2-(2-BUTOXYETHOXY)ETHANOL</b>  |              |   |
| CAS   | 112-34-5     | $0,1449 \leq x < 0,1658$ Eye Irrit. 2 H319  |
| EC  | 203-961-6    |   |
| INDEX   | 603-096-00-8 |   |
| <b>2-metil-4-isotiazolin-3-one</b>  |              |   |
| CAS   | 2682-20-4    | $0,006 \leq x < 0,0089$ Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411                         |
| EC  | 220-239-6    |   |
| INDEX   |              |   |
| <b>1,2-benzisothiazol-3(2H)-one</b>   |              |   |
| CAS   | 2634-33-5    | $0,006 \leq x < 0,0089$ Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411   |
| EC  | 220-120-9    |   |
| INDEX   | 613-088-00-6 |   |
| <b>5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one</b> |              |   |
| CAS   | 55965-84-9   | $0,0017 \leq x < 0,0028$ Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1 |
| EC  |              |   |
| INDEX   | 613-167-00-5 |   |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 3 / 10

### SECTION 5. Firefighting measures ... / >>

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE

#### EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 4 / 10

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

|     |                |   |
|-----|----------------|---|
| ESP | España         | LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)  |
| FRA | France         | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS  |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Third edition, published 2018)   |
| ITA | Italia         | DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017   |
| NOR | Norge          | Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5 |
| POL | Polşa          | ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r   |
| EU  | OEL EU         | Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.                           |
|     | TLV-ACGIH      | ACGIH 2019  |

#### QUARTZ

##### Threshold Limit Value

| Type      | Country | TWA/8h |      | STEL/15min |     | Remarks / Observations |
|-----------|---------|--------|------|------------|-----|------------------------|
|           |         | mg/m3  | ppm  | mg/m3      | ppm |                        |
| VLA       | ESP     |        | 0,05 |            |     | RESP                   |
| VLEP      | FRA     | 0,1    |      |            |     | RESP                   |
| TLV       | NOR     | 0,1    |      |            |     | RESP                   |
| NDS/NDSch | POL     | 0,1    |      |            |     | RESP                   |
| TLV-ACGIH |         | 0,025  |      |            |     |                        |

#### 2-(2-BUTOXYETHOXY)ETHANOL

##### Threshold Limit Value

| Type      | Country | TWA/8h |     | STEL/15min |     | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |                        |
| VLA       | ESP     | 67,5   | 10  | 101,2      | 15  |                        |
| WEL       | GBR     | 67,5   | 10  | 101,2      | 15  |                        |
| VLEP      | ITA     | 67,5   | 10  | 101,2      | 15  |                        |
| TLV       | NOR     | 68     | 10  |            |     |                        |
| NDS/NDSch | POL     | 67     |     | 100        |     |                        |
| OEL       | EU      | 67,5   | 10  | 101,2      | 15  |                        |
| TLV-ACGIH |         | 66     | 10  |            |     |                        |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

##### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 5 / 10

### SECTION 8. Exposure controls/personal protection ... / >>

threshold values considered. The protection provided by masks is in any case limited. If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

| Properties                             | Value             | Information |
|--|-------------------|-------------|
| Appearance                             | paste             |             |
| Colour                                 | white             |             |
| Odour                                  | characteristic    |             |
| Odour threshold                        | Not available     |             |
| pH                                     | 8 - 9             |             |
| Melting point / freezing point         | Not available     |             |
| Initial boiling point                  | Not available     |             |
| Boiling range                          | Not available     |             |
| Flash point                            | > 60 °C           |             |
| Evaporation Rate                       | Not available     |             |
| Flammability of solids and gases       | Not available     |             |
| Lower inflammability limit             | Not available     |             |
| Upper inflammability limit             | Not available     |             |
| Lower explosive limit                  | Not available     |             |
| Upper explosive limit                  | Not available     |             |
| Vapour pressure                        | Not available     |             |
| Vapour density                         | Not available     |             |
| Relative density                       | 1,08              |             |
| Solubility                             | MISCIBLE IN WATER |             |
| Partition coefficient: n-octanol/water | Not available     |             |
| Auto-ignition temperature              | Not available     |             |
| Decomposition temperature              | Not available     |             |
| Viscosity                              | Not available     |             |
| Explosive properties                   | not applicable    |             |
| Oxidising properties                   | Not available     |             |

#### 9.2. Other information

Total solids (250°C / 482°F) 9,37 %

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 6 / 10

### SECTION 10. Stability and reactivity ... / >>

#### 10.5. Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

#### 10.6. Hazardous decomposition products

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

### SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

##### Interactive effects

Information not available

##### ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Oral)

3384 mg/kg Rat

LD50 (Dermal)

2700 mg/kg Rabbit

##### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

##### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

##### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

May produce an allergic reaction.

Contains:

2-metil-4-isotiazolin-3-one

1,2-benzisothiazol-3(2H)-one

##### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

##### CARCINOGENICITY



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 7 / 10

### SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

#### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

|                           |                   |
|---------------------------|-------------------|
| 2-(2-BUTOXYETHOXY)ETHANOL |                   |
| Solubility in water       | 1000 - 10000 mg/l |
| Rapidly degradable        |                   |

#### 12.3. Bioaccumulative potential

|  |   |
|--|---|
| 2-(2-BUTOXYETHOXY)ETHANOL              |   |
| Partition coefficient: n-octanol/water | 1 |

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.







# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 9 / 10

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                          |  |
|--------------------------|--|
| <b>Acute Tox. 2</b>      | Acute toxicity, category 2   |
| <b>Acute Tox. 3</b>      | Acute toxicity, category 3   |
| <b>Acute Tox. 4</b>      | Acute toxicity, category 4   |
| <b>STOT RE 2</b>         | Specific target organ toxicity - repeated exposure, category 2     |
| <b>Skin Corr. 1B</b>     | Skin corrosion, category 1B  |
| <b>Eye Dam. 1</b>        | Serious eye damage, category 1                                     |
| <b>Eye Irrit. 2</b>      | Eye irritation, category 2   |
| <b>Skin Irrit. 2</b>     | Skin irritation, category 2  |
| <b>Skin Sens. 1</b>      | Skin sensitization, category 1                                     |
| <b>Skin Sens. 1A</b>     | Skin sensitization, category 1A                                    |
| <b>Aquatic Acute 1</b>   | Hazardous to the aquatic environment, acute toxicity, category 1   |
| <b>Aquatic Chronic 1</b> | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| <b>Aquatic Chronic 2</b> | Hazardous to the aquatic environment, chronic toxicity, category 2 |
| <b>H330</b>              | Fatal if inhaled.  |
| <b>H301</b>              | Toxic if swallowed.  |
| <b>H311</b>              | Toxic in contact with skin.  |
| <b>H331</b>              | Toxic if inhaled.  |
| <b>H302</b>              | Harmful if swallowed.  |
| <b>H373</b>              | May cause damage to organs through prolonged or repeated exposure. |
| <b>H314</b>              | Causes severe skin burns and eye damage.                           |
| <b>H318</b>              | Causes serious eye damage.   |
| <b>H319</b>              | Causes serious eye irritation.                                     |
| <b>H315</b>              | Causes skin irritation.  |
| <b>H317</b>              | May cause an allergic skin reaction.                               |
| <b>H400</b>              | Very toxic to aquatic life.  |
| <b>H410</b>              | Very toxic to aquatic life with long lasting effects.              |
| <b>H411</b>              | Toxic to aquatic life with long lasting effects.                   |

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament



# SPIVER S.r.l.

## THERMOFLEX ONE

Revision nr.7  
Dated 25/02/2020  
First compilation  
Printed on 25/02/2020  
Page n. 10 / 10

### SECTION 16. Other information ... / >>

3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

#### Changes to previous review:

The following sections were modified:

02 / 03 / 09.