



Ardore



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

A valuable finish of top class interior decoration, effect FLASH-PEARL. Which allows you to obtain, with a very simple application, a unique "brand" result of extraordinary beauty. ADORE is particularly suitable in environments of modern setting and / or neoclassical where refined elegance is requested, both in public places and private homes. ADORE is washable after about three weeks from the application, non-flammable and provides good water vapour permeability.

2. COMPOSITION

Organic and Inorganic pigments, acrylic copolymer emulsion, special non-toxic additives. And 'free from harmful Substances such as solvents and pigments containing lead or chrome.

3. METHOD OF APPLICATION

Surface preparation

Sandpaper and dust any imperfections with STUCCOMURO and apply 1 coat of UNIVERSALFISSATIVO, which should be correctly diluted with water at a ratio of 1:5 up to 1:10 according to the absorption of the surface. Leave to dry for at least 4 hours and apply 1 or 2 coats of PRIMER S of the color Z-90, leave at least 4 to 5 hours between each application.

Preparation for Mixing.

Add 70 ml. Of ARTHE CONCENTRATO of the colour chosen, mix slowly by hand all the product and it is then ready for

use. (The mixed product has a pot-life of about 15 days).

Application

Spread ADORE with a SPALTER DECORA' tool on the surface using irregular movements like criss crossing brush marks Wait 20 minutes and start to give the first pressing with a stainless steel trowel. After 10 minutes go back over the applied surface putting pressure on the stainless steel trowel using the same movements as before

4. TECHNICAL DATE

SPECIFIC WEIGHT: 1,020 +/-

5% kg/Lt

COLOR: Colours from the color chart

VISCOSITY: Thixotropic look.

YIELD: 10 m²/Lt. More or less.

APPLICATION TEMPERATURE: between 8°C and 30°C.

FILM ASPECT: MATT.

DILUTION: Ready to use (do not dilute).

PACKAGING: Lt. 2,5 polyethylene containers.

DRYING: To touch 4-5h, completely 24-48h at 20°C.

APPLICATION: Spread with a brush and finish with a stainless steel trowel.

PRESERVATION: 24 months in the intact packages, away from temperature changes.

HS-CODE: 32149000

5. ITEM OF SPECIFICATIONS

INTERNAL USE

Decoration and protection of interior wall surfaces with decorative effect oxide, the type of GLOWING Spiver Ltd. , Based on inorganic and organic

pigments, acrylic copolymers in emulsion, special non-toxic additives, after suitable treatment of the support with PRIMER S tint indicated in the folder. Price includes materials and implementation, excluding the scaffolding sqm. €

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it