

Decorative Paint - Italian Style

Cocciopesto

1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

COCCIO PESTO is a natural decorative stucco in paste obtained thanks the to combination of old recipes and new technologies allowing to obtain dotted marble-like semimatt finishes with special shades realized through to the presence of cocciopesto grains. product is endowed with an excellent perspiration and extraordinary anti-mould power (thanks to the disinfectant power of lime), it can be applied on both external and internal walls. It hardens in consequence of the chemical process of carbonatation: the calcium hydroxide (primary binder of the product) reacts with the carbonic anhydride present in the air by producing calcium carbonate, which is marble's main component (hence the name "marmorino"). Thanks to its features, it is largely employed as an elegant finishing for all prestige environments.

2.COMPOSITION

Long-seasoning micronized slaked lime, cocciopesto, high-selected calcareous filler, non-toxic additives.

COLOURING

Each article in our color chart has been divided into 4 different grades, each one corresponds to a letter A, B,C,D

In order to obtain the desired color you must add in each pack of COCCIO PESTO of Lt.14, the quantity of ARTHE toner as indicated in the chart below:

Art. A	Art. B	Art. C	Art. D
3 X	1 x	3 x	1 x
600ml	600 ml	70 ml	70 ml

3.METHODS OF APPLICATION INTERNAL USE

The application on lime supports is recommended, but it can also be applied on plaster or byproducts, old hydropaints, only if strong and well-fixed, after the application of one coat of Primer Extra, diluted whit water in the ratio of 1 to 7, or Primer RV for hard supports (such as plasterboard, cellular cement, baked clay, etc.).

- 1. Spread a coat of COCCIO PESTO with a stainless steel smoother so as to level the support; if needed, spread a second coat.
- 2. Apply a second coat of COCCIO PESTO so as to obtain a perfectly smooth effect. Once the product is almost dry, press slightly and polish with a clean stainless steel smoother so as to show off all the shades deriving from the crushing of the cocciopesto grains. Do not apply protective wax.

EXTERNAL USE

It can be applied only on plasters bound with slaked lime and without cement; do not apply on supports where rising damp is present.

- Wet the support plaster;
- 2. Repeat points 1 and 2 of the internal use instructions;
- Apply a coat of REPSIL 07 (non-filming silossanic protective) with spray or paint-brush to give the finishing a high resistance to the atmospheric agents.



4.TECHNICAL DATA SPECIFIC WEIGHT:1,550 - kg/lt.

+/-0,5%

VISCOSITY:highly thixotropic

paste

DRYING:2 hours to the touch at 20°C - completely dry in 24 hours at 20°C

TEMPERATURE OF APPLICATION: between 30°C and 30°C YIELD: 1,1 - 1,5 mq./Lt. (on a

smooth support treated with Primer RV PACKAGE:14–5–2,5 litres

polyethylene-containers

COLOURS:to be chosen in the

catalogue

PRESERVATION: 24 months in the intact packages away from temperature changes

HS-CODE: 32149000

5.ITEM OF SPECIFICATIONS

Protective decoration of walls with stucco having a marble-like effect, like COCCIO PESTO produced by Spiver Ltd., containing long-seasoning micronized slaked lime, high-selected calcareous filler, non-toxic additives and pigments with a high resistance to light and alkalis, prior a correct treatment of the support. Price inclusive of the material and implementation, except the scaffoldings per square metre: €

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122 93100 Caltanissetta (CL) Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Technical Data Sheet: Cocciopesto SP044. Rev.1 This sheet supersedes the previous