



Nobilis



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

A unique coating moldable material, for the high interior decoration, based on pure metal bound by a special resin hi-tech. The tenacity of the Platinum, Gold exuberance, the determination of copper, the compactness of the Bronze and the temper of Palladio, are the five elements that characterize NOBILIS, and give it an absolute authenticity value, which has never been achieved by any other wall finishing, until now present in the market high decoration. NOBILIS gives a magical transformation to any surface, in a finish-emotion pure and precious metal, visible, feel and touch. With its original and exclusive appearance NOBILIS illuminates and enhances any wall or artifact, it allows the decorator to give creative solutions and proposals of extraordinary beauty and absolute exclusivity. It can be applied as an added value to environments and / or sites of high attractions and prestige, both in private homes, which in public projects. High washable resistance, resistant to fungus and bacteria.

2. COMPOSITION

Special epoxy-polyamide resin compound in aqueous emulsion, powders of special metal powder superficially treated, reinforcing fillers, additives.

3. METHOD OF APPLICATION

Preparation of the surface.

Wall surfaces pretreated with a coat of PRIMER S diluted with

30% water, to dry at least 24 h.

Preparation of the product.

Mix with electric mixer, NOBILIS comp. A and NOBILIS comp. B for about 3 minutes, then add with agitation produced in the NOBILIS COLOURS of the chosen color, taking utmost care of mixing perfectly.

Product life

After perfectly mixing of the three components, the compound must be used within 30 and 60 minutes, depending on the temperature of application.

Applying the product.

NOBILIS, once mixed, is presented as a soft modeling clay, applied with a steel trowel, which allows the decorator an unlimited amount of techniques and fantasies.

Grinding, sanding, polishing

1st STAGE

For the first roughing, and sculpting of the application.

Use the following succession of polishing with abrasive discs, by 220, 320, 400, respectively.

Minimum initial speed, gradually increase in the consumption function and verification of the status of the abrasive disc.

2nd STAGE

Smoothing and the leveling of the effect with the succession of polishing with abrasive discs, 500, 800

Start at medium speed, gradually increasing until reaching a maximum speed.

3rd STAGE

Mirror polishing with the succession of polishing with abrasive discs, 1500, 3000, 6000

Minimum speed of execution.

4th STAGE

Polishing with POLISH (type BLU 3M) with rotary buffer starting at low speed, gradually increasing up to a medium speed.

5th STAGE

The final cleaning can be done by hand with a paper towel, with the help of a mild degreasing detergent diluted 50% with water.

4. TECHNICAL DATA

SPECIFIC WEIGHT comp.A:

1,120 Kg./Lt. +/- 5%

SPECIFIC WEIGHT comp.B

1,030 Kg./Lt. +/- 5%

SPECIFIC WEIGHT COLOUR

PLATINO: 2,5 - 3,0 Kg./Lt.

SPECIFIC WEIGHT COLOUR

RAME: 3,2 - 4,5 Kg./Lt.

SPECIFIC WEIGHT COLOUR

GOLD : 3,0 - 4,0 Kg./Lt.

SPECIFIC WEIGHT COLOUR

BRONZO: 3,2 - 4,5 Kg./Lt.

SPECIFIC WEIGHT COLOUR

PALLADIO: 3,5 - 4,9 Kg./Lt.

DILUTION: ready to use, for smooth application you can dilute with 5-10% with water.

APPLICATION: Stainless trowel, then use a brush, roller or spray.

MIXING RATIO:

10,22%

componente A, 9,90%

componente B, 79,87 %

componente C

DRYING TO TOUCH:

24 hours

at 20°C

WASHABLE:

after 48 hours at

20°C

APPLICATION TEMPERATURE:

between 10°C and 30°C.

REACTION TO FIRE: negative if the product is applied a non-flammable surface; water base material with a thickness less than 0,600 exact.

YIELD: varies between 1 and 2 kg per square metre. (Depending on



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it



Nobilis



the thickness desired)

COLOUR: from the colour chart.

PACKAGE: kit kg. 6,260 (A+B+C)

polyethylene containers.

PRESERVATION: 24 months in

the intact packages, away from

temperature changes.

HS-CODE:

HS-CODE NOBILIS: 32149000

HS-CODE COLOURS PLATINO:

80070080

HS-CODE COLOURS RAME:

74061000

HS-CODE COLOURS ORO:

74061000

HS-CODE COLOURS BRONZO:

74061000

HS-CODE COLOURS

PALLADIO: 74061000

5.SPECIFICATION

Decoration of interior wall

surfaces with effect finish "pure

metal" type of NOBILIS SPIVER

Srl, with consumption of about 1.5

kg. x m², after the application of

one coat of anchor PRIMER S

SPIVER Srl.

Price includes materials and

implementation, excluding the

scaffolding m² €

N.B. The above data may be subject to change. The Spiver S.r.l. assumes no responsibility for the negative results that depend on applications running outside of its control or due to elements other than the quality of the product.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Scheda Tecnica: Nobilis SP104. Rev.1 La presente scheda annulla e sostituisce le precedenti