



## TEKNOSYL

### 1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Silicate paint for outdoor use for protecting and decorating new and old buildings. The main features of TEKNOSYL are as follows:

- Excellent adhesion to all types of media;
- Good degree of breathability;
- Excellent water repellency;
- Resistance to weather, light and UV rays.

### 2. COMPOSITION

Silicates, limestone microfillers, special reinforcing extenders, special iron and / or titanium oxides stable to U.V. And alkalis, additives.

### 3. METHOD OF APPLICATION

Lime and / or cement mortars surfaces are suitable, mineral or synthetic paintings and finishes, perfectly dry and cohesive. Do not apply on supports where there is evidence of rising or infiltrating humidity

Apply a coat of SPIVERSIL PRIMER diluted 1: 1 in water; After 12 hours, apply a first coat as a primer of TEKNOSYL diluted with 20% of water with a roller. After 12 hours, apply the second coat of TEKNOSYL with a roller, maximum dilution of 5% to 15% with water, depending on the degree of filling desired.

### 4. TECHNICAL DATA

**SPECIFIC WEIGHT:** 1570 gr./lt +/- 5%

**DRYING:** to touch 2 hours at 20°C; **completely dry** :about 24 ore at 20°C

**APPLICATION TEMPERATURE:** between 5°C and 30°C

**APPLICATION:** Sponge Roller hair Roller, brush or spray.

**COVERAGE** 2,5 – 3 m<sup>2</sup>/Lt (two coats)

**COLORS:** White

**TINTING:** Coloring can also be achieved by the tinting system: Global Tinting System.

**PACKAGE:** polyethylene cans LT14

**DILUTION:** 0-20% with water depending on the job.

**PRESERVATION:** 24 months in the intact packages, away from temperature changes.

**HS-CODE:** 32091000

### 5. ITEM OF SPECIFICATIONS

Decoration and protection of external and internal surfaces with silicate paint of Spiver s.r.l. type TEKNOSYL, silicon-based calcareous micro fillers, special reinforcing extenders, special ferrous and / or titanium alloys stable to U.V. And alkalis, additives, with the application of a primer of primer SPIVERSIL PRIMER of Spiver S.r.l., on a regular plaster coat with RASANTE-W04.

Price including material and installation, excluding scaffoldings per square meter. € .....

N.B. The above data may be subject to change. Spiver srl assumes no responsibility for the negative results that depend on applications running outside of its control or due to causes unconnected to the quality of the product



*Emotion with paint ...*

**SPIVER s.r.l.**

contrada Babbaurra S.S. 122

93100 Caltanissetta ( CL )

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

[www.spiver.it](http://www.spiver.it) - [info@spiver.it](mailto:info@spiver.it)

**Scheda Tecnica: TEKNOSYL - SP111 Rev.1** La presente scheda annulla e sostituisce le precedenti