

Genyus Ultramatt



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Interior and exterior wall water-based paint. Highly opaque with excellent coverage, extra-washable and high whiteness. Application procedure is very easy with anti-drip when applying by roller and self-dilating when applying by brush. GENYUS Ultramatt is extremely suitable where strong light shows up small imperfections and you have the obvious need to hide them. Thanks to its exceptional opacity (<1.5 at 85 ° gloss) GENYUS Ultramatt, almost completely prevents the problems of light reflecting on very smooth surfaces, where it also allows perfect repairing. Applicable on all types of surfaces such as plaster, lime and / or cement, old paint (after appropriate preparation), but is mainly used on plasterboard surfaces, where it extraordinary eliminates several problems of reflection and allows immediate coverage, maintaining a remarkable elegant touch.

2.COMPOSITION

Titanium dioxide, synthetic copolymers in emulsion alkali resistant, micronized fillers, special reinforcing fillers and super-matting, non-toxic additives. It is free from harmful substances such as lead-based or chrome solvents and pigments.

External wall paint, silicate base suitable for the protection and decoration of new and old buildings. The main features of TEKNOSYL are as follows:

- Excellent adhesion to all types of surfaces;
- Good level of breathability;
- Excellent water repellence;
- Weather resistance, to light and UV rays.

3.METHOD OF APPLICATION

Sandpaper, dust and fill any imperfections with STUCCOMURO (so it can be completely smoothed), then apply UNIVERSAL FISSATIVO diluted with water, ratio of 1:15 according to the absorption of the surface. On plasterboards, after having primed the filled any imperfections, you can apply directly. Allow drying for at least 4 hours and then apply two coats of water-based paint GENYUS Ultramatt appropriately diluted (see technical data), leaving 4 to 5 hours between each coat.

4. TECHNICAL DATA

SPECIFIC WEIGHT:: 1400g/Lt. ±30g/Lt.

FILM ASPECT: HIGHLY MATT

COLOR: White

COLOURING: The colours can be obtained by using the

Global Tinting System.

VISCOSITY: thixotropic

COVERAGE : 7-8 m²/Lt. (two coats)

DILUTION: 40-50% with water for brush application, 60% for application with roller or spray application.

DRYING: dry to the touch 30 minutes, completely dry: 24 hours at 20°C

APPLICATION: Brush, roller, spray

PACKAGE: Lt. 14, Lt5, and Lt 2.5 polyethylene cans

PRESERVATION: 36 months in the intact packages, away

from temperature changes.

WASHING RESISTANCE (Method UNI 10765):

- Classification: Excellent resistance to washing
- Brushstrokes: ≥ 5000

ABRASION RESISTANCE WET EN 13300):

Resistance: Class 2

WATER VAPOR PERMEABILITY: medium, class 2, Sd from ≥ 1.4 to ≤ 0.47 (UNI EN ISO 7783-2).

HS-CODE : 32091000

5.ITEM OF SPECIFICATIONS

Indoor wall surfaces water-based paint extra-washable highly opaque of GENYUS Ultramatt by SPIVER srl applied in two coats with a brush, roller or spray with average consumption of 0,150 Lt./m², after the application of one coat of UNIVERSAL PRIMER, SPIVER, diluted with water in a ratio of 1:10 up to 1:15 depending on the absorption of support. Price includes materials and implementation, excluding the scaffolding sqm €

N.B. The above data may be subject to change. Spiver srl assumes no responsibility for the negative results that depend on applications running outside of its control or due to causes unconnected to the quality of the product.



Emotion with paint ...

SPIVER s.r.l.

contradaBabbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it