



Genyus Special



1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Extra-washable wall water paint for both interiors and exteriors with a fine velvety aspect, excellent covering power, excellent whiteness, easily applicable thanks to its roller anti-drop effect and its brush self-expanding effect. GENIUS SPECIAL can be applied on any kind of support, such as: plaster, plasterboard, lime and/or cement-based targets, old water paints (prior adequate preparation).

2.COMPOSITION

GENIUS SPECIAL contains titanium dioxide, alkali-resistant synthetic copolymers in emulsion, hypermicronized charges, special reinforced fillers, non-toxic additives. It does not contain any noxious substance, such as lead or chrome-based solvents and pigments.

3.METHODS OF APPLICATION

Sand, dust and plaster over any imperfection using STUCCOMURO or POLISTUCK (depending on the thickness of the imperfection); then apply a coat of FISSATIVO UNIVERSALE opportunely diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10, depending on the absorption degree of the support. Let the product dry for at least 4 hours and apply two coats of water paint GENIUS SPECIAL, opportunely diluted (see technical data), at a distance of 4/5 hours after the application of the first coat.

4.TECHNICAL DATA

SPECIFIC WEIGHT: 1393 +/- 5% grams/litres
FILM ASPECT: MATT
COLOURS: white (and other colours on demand)
VISCOSITY: thixotropic aspect
YIELD: 8/9 m²/litres (for two coats)
DILUTION: 40%/50% in water, to be applied with a brush or roller 60%, to be applied with a spray-gun
PACKAGE: 14-litres tinplated cases available 5 / 2,5-litres polyethylene cases available
DRYING: dry to the touch: 30 minutes completely dry: 24 hours at 20°C
APPLICATION: brush, roller, spray
PRESERVATION: 36 months in the intact packages, away from temperature changes
HS-CODE : 32091000

Painting of interior walls with extra-washable water paint with a velvety aspect, like GENIUS SPECIAL, produced by Siver Ltd., applied in two coats using a brush, roller or spray-gun with an average consumption of 0,15 litre/ m², prior application of a coat of FISSATIVO UNIVERSALE, produced by Siver Ltd., diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10, depending on the absorption degree of the support. Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

N.B. The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.

5.ITEM OF SPECIFICATIONS



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it