



## Colombina



### 1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Wall thixotropic tempera water-based paint for high covering interiors having an excellent filling power, a good resistance to the rubbing without mortar and an high perspiration degree. It can be brushed on all types of supports such as: plaster, plasterboard, lime and/or cement-based pargets, old water paints (after proper preparation).

### 2.COMPOSITION

Titanium dioxide, polyacetovinilic copolymers in emulsion, crystalline carbonates, highly selected amorphous, special extenders and non-toxic additives.

### 3.METHODS OF APPLICATION

Sand, clean, plaster over any imperfection with STUCCOMURO or with POLISTICK (depending on the thickness of the imperfection). Apply a coat of FISSATIVO UNIVERSALE diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10, according to the absorption degree of the support. Let it dry for at least 4 hours and apply two coats of water paint COLOMBINA, opportunely diluted, (see the technical data) at 4-5 hours intervals.

### 4.TECHNICAL DATA

**SPECIFIC WEIGHT:** 1540 +/- 30 grams/litres;  
**FILM ASPECT:** MATT;  
**COLOURS:** white (other colours by request);  
**VISCOSITY:** thixotropic aspect;  
**YIELD:** 6-7 m<sup>2</sup>/litres (by two coats);  
**DILUTION:** 40-50% in water for paintbrush and roller application; 60% in water for spray application;  
**PACKAGE:** 14/ 5/ 2,5 litres polyethylene cases available;  
**DRYING:** to the touch 30 minutes, completely 24 hours at 20°C;  
**APPLICATION:** paintbrush, roller, spray;  
**PRESERVATION:** 36 months in the intact packages, away from temperature changes;  
**HS-CODE :** 32091000.

### 5.ITEM OF SPECIFICATIONS

Painting of indoor walls using Polyacetovinil copolymers based water paints in emulsion like COLOMBINA produced by SPIVER Ltd., applied by two paintbrush, roller or spray coats with an average consumption of 0.150 litres/m<sup>2</sup>, previous application of a

coat of FISSATIVO UNIVERSALE produced by SPIVER Ltd., diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10 according to the support absorption degree. Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality



*Emotion with paint ...*

**SPIVER s.r.l.**

contrada Babbaurra S.S. 122  
93100 Caltanissetta ( CL )

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

[www.spiver.it](http://www.spiver.it) - [info@spiver.it](mailto:info@spiver.it)