



Pittura Extra



1.SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Wall water-based paint for high covering interiors having an excellent filling power, a good resistance to the washing and rubbing and a high perspiration degree. It can be brushed on all types of supports such as: plaster, plasterboard, lime and/or cement-based targets, old water paints (after proper preparation).

2.COMPOSITION

Titanium dioxide, polyacetovinyl copolymers in emulsion, crystalline carbonates, highly selected amorphous, special extenders and non-toxic additives. It does not contain any noxious substance such as lead and chrome-based solvents and pigments.

3.METHODS OF APPLICATION

Sand, clean out, plaster any imperfection with STUCCOMURO or with POLISTICK (depending on the thickness to be levelled). Apply a coat of FISSATIVO UNIVERSALE diluted in water from a ratio of 1 to 5 to a ratio of 1 to10, according to the absorption degree of the support. Let it dry for at least 4 hours and apply two coats of water paint PITTURA EXTRA, opportunely diluted, (see the technical data) at 4-5 hours intervals.

4.TECHNICAL DATA

SPECIFIC WEIGHT: 1540 +/- 30 grams/litres
FILM ASPECT: MATT
COLOURS: white (other colours by request)
VISCOSITY: thixotropic aspect
YIELD: 6-7 m²/litres (by two coats)
DILUTION: 40-50% in water for paintbrush and roller application; 60% in water for spray application
PACKAGE: 14/ 5/ 2,5 litres polyethylene cases available
DRYING: to the touch 30 minutes, completely 24 hours at 20°C
APPLICATION: paintbrush, roller, spray
PRESERVATION: 36 months in the intact packages, away from temperature changes
HS-CODE : 32091000

5.ITEM OF SPECIFICATIONS

Painting of indoor walls using Polyacetovinyl copolymers based water paints in emulsion like the PITTURA EXTRA produced by SPIVER Ltd., applied by two paintbrush, roller or spray coats with an average consumption of 0.150 litres/m², prior application of a coat

of FISSATIVO UNIVERSALE produced by SPIVER Ltd., diluted in water from a ratio of 1 to 5 to a ratio of 1 to10, according to the absorption degree of the support. Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122
93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it