



Multigum

1. CHARACTERISTICS AND FIELDS OF USE

Colored liquid waterproofing membrane. It is used for waterproofing terraces, retaining walls and in all cases where there have been problems of infiltration into the water of atmospheric origin. Good elasticity and adhesion on the substrate. A completed work forms a continuous colored layer, free of any form of welding and above all of cracking, unalterable to the U.V. and atmospheric agents. Product not suitable for waterproofing concrete water tanks and swimming pools or surfaces with permanent contact with water.

2. COMPOSITION

Styrene-acrylic emulsion, lamellar extenders, iron and / or titanium oxides, additives.

3. APPLICATION METHOD

Perfectly dust the surface and make sure that the substrate is dry and free from traces of grease and oils. On cementitious substrates it is necessary to 'prime' the base with a coat of DERASOL H2O diluted 1: 1 with water (on MULTIGUM asphalt, no priming is required). Apply MULTIGUM in two / three coats, without any dilution, spaced 24 hours apart. For a good result of the works we recommend a final thickness of not less than 1mm.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,290 Kg./Lt +/- 5%.

COLORS: white, light gray, brick red and other colors on request.

TINTING: The colors can be obtained through the tinting system: Global Tinting System.

VISCOSITY: thixotropic paste

YIELD: 2 m²./Lt.x1mm. thick.

PACKAGING: containers in plt. from Lt. 13, Lt. 5, Lt. 2,5, ml. 750.

DRYING TIME: to the touch 2h at 20 ° C, in depth 24h at 20 ° C.

APPLICATION TEMPERATURE: between 10 ° C and 30 ° C.

WALKABILITY: 72 hours from application at 20 ° C.

APPLICATION: brush, roller, spray.

STORAGE: 36 months in unopened packages protected from temperature changes.

HS-CODE: 32091000

5. SPECIFICATION ITEM

Waterproofing treatment on a cementitious support with MULTIGUM type styrene-acrylic liquid membrane of Spiver S.r.l. applied in two / three coats without dilution, after suitable priming with DERASOL H2O type high-penetration anti-alkali solvent-based fixative of SPIVER S.r.l. . Price including material and installation, excluding scaffolding per m² €

N.B. The above data may be subject to change. Spiver S.r.l. assumes no responsibility for negative results that depend on applications performed outside of its control or which depend on factors unrelated to the quality of the product.



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Scheda Tecnica: Multigum SP 084. Rev.1 La presente scheda annulla e sostituisce le precedenti