

	<h1>STUCCOMURO</h1>	<b>SPECIFICATIONS</b>
		Rev. 0 – Ed. 1

### SPECIFICATIONS AND FIELDS OF EMPLOYMENT

STUCCOMURO is a finishing stucco in paste for interiors specifically employed for the levelling and smoothing of walls. It is characterized by a good filling power, an excellent whiteness and it can be easily applied and sandpapered.

### COMPOSITION

Highly-selected fillers, cellular and synthetic binders, additives.

### METHODS OF APPLICATION

Apply the product (ready for use) with a metallic float. Let the product dry and sandpaper the support.

### TECHNICAL DATA

SPECIFIC WEIGHT:	1,650 kg/Lt. +/- 0,5%
VISCOSITY:	thixotropic paste
YIELD:	not applicable
DILUTION:	ready for use (max 5% with water)
PACKAGE:	20Kg.-polyethylene cases available
DRYING:	completely dry in 24 hours at 20°C
OVERPAINTING DEGRE:	24 hours
APPLICATION:	metallic float
PRESERVATION:	36 months in the intact packages, away from temperature changes

### ITEM OF SPECIFICATIONS

Smoothing treatment of wall surfaces with the application of one coat of stucco in paste like STUCCOMURO produced by Spiver Ltd.

Price inclusive of the material and implementation, except the scaffoldings per square metre: €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.