Decorative Paint - Italian Style

MARMOPERLA



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Granular decorative wall covering in paste with a motherof-pearl marble effect.

Its wonderful pearlescent gives a particular depth to the walls and a seductive touch, of exclusive elegance and refinement, which remains fully balanced and never

Good breathability, excellent water repellence, resistant to mould.

It is used as a high decoration finish and furnishing in luxurious public and private spaces.

MARMOPERLA is a product of great ductility, allowing with a single product to obtain various effects and solutions.

2. COMPOSITION

Mixed emulsion with synthetic matrix, mix of natural and synthetic bios table micas, limestone filler with controlled granulometry, organic and inorganic pigments, water repellent, biocide free from donor formaldehyde, other non-toxic additives

3. MODALITA' D'APPLICAZIONE

We recommend the application on new mineral substrates, but it can also be applied on gypsum or byproducts, old water-based paints if strong and well anchored, after applying a coat of DERASOL H2O diluted with water in a 1 to 1 ratio, or Primer S for substrates difficult to adhere to (old washable paints, plasterboard, cellular concrete, ceramic, etc.) MARMORINO EFFECT

1) Spread a layer of MARMOPERLA with a stainless steel float and level the support; if necessary repeat the procedure with another layer. 2) Spread another layer of MARMOPERLA taking care to obtain an absolutely smooth surface. As soon as the product tends to dry, apply small pressure to the trowel with a clean stainless steel trowel in order to smooth and compact the surface, thus obtaining a smooth and silky surface.

Thanks to its excellent workability MARMOPERLA allows to obtain various decorative solutions: Travertine effect, Favignana effect, Horizon effect, Majolica effect,

4.TECHNICAL DATA

SPECIFIC WEIGHT: 1,480 +/-5% Kg. /Lt.

VISCOSITY': tixotropic Paste

DRYING to touch: 2 hours at 20°C. DRYING Completely: 24 hours at 20°C.

APPLICATION TEMP: between 10°C and 30°C.

COLOURS: From the colour chart. **APPLICATION:** Brush or Spray

COVERAGE: 1,25 - 1,50 m²/Kg. (two coats)

TINTING: The colours can also be obtained through the

tinting system

PRESERVATION: 24 months in the intact packages

away from temperature changes.

HS-CODE: 32149000

5.ITEM OF SPECIFICATIONS

Decoration and protection of wall surfaces with motherof-pearl marmorino effect plaster, of the MARMOPERLA type of Spiver s.r.l., mixed emulsion with synthetic matrix, limestone filler with controlled granulometry, organic and inorganic pigments, water repellent, biocide free from formaldehyde donors, other non-toxic additives, after suitable support treatment. Price including material and installation, excluding scaffolding per sq. M. €

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality



Emotion with paint ...

SPIVER s.r.l.

contrada Babbaurra S.S. 122 93100 Caltanissetta (CL) Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Technical Data Sheet: Marmoperla SP 129 Rev.1 This document replace all before documents